

Strapbinder stainless steel banding is available in Type 201, 304 or 316 stainless steel. Strapbinder stainless is ideal for large diameter hose assemblies, sign securement, insulation applications and general construction use. It is made with a full round edge for safer handling.

Type 201 Stainless Steel Type 201 stainless steel has excellent mechanical properties and strength. Due to its high work hardening rate, it possesses uniform elongation for improved stretch ability for severe forming applications such as strapping bands and preformed hose clamps.

Type 304 Stainless Steel Type 304 stainless steel is an 18% chromium and 8% nickel alloyed stainless steel. Used most often in outdoor industrial applications, it offers good corrosion resistance and is weldable.

Type 316 Stainless Steel Type 316 stainless steel provides superior corrosion resistance, making it ideal for use near salt water and petrochemical facilities.

100 ft. Self Dispensing Coils

Item#	Width	Material	Thickness	Weight	Quantity
				Each	
ST202	1/4 in	Type 201 Stainless Steel	.020 in	1.7 lb	100 ft/Roll
	6.35 mm		.51 mm	0.9 kg	
ST203	3/8 in	Type 201 Stainless Steel	.025 in	3.2 lb	100 ft/Roll
	9.53 mm		.63 mm	1.6 kg	
ST204	1/2 in	Type 201 Stainless Steel	.030 in	5.1 lb	100 ft/Roll
	12.70 mm		.76 mm	2.4 kg	
ST205	5/8 in	Type 201 Stainless Steel	.030 in	6.4 lb	100 ft/Roll
	15.88 mm		.76 mm	3.0 kg	
ST206	3/4 in	Type 201 Stainless Steel	.030 in	7.7 lb	100 ft/Roll
	19.05 mm		.76 mm	3.6 kg	
ST404	1/2 in	Type 316 Stainless Steel	.030 in	5.1 lb	100 ft/Roll
	12.70 mm		.76 mm	2.4 kg	
ST406	3/4 in	Type 316 Stainless Steel	.030 in	7.7 lb	100 ft/Roll
	19.05 mm		.76 mm	3.6 kg	



Plastic Totes (Type 201 Stainless Steel)

		· · · · · · · · · · · · · · · · · · ·			
ltem #	Width	Tote Color	Thickness	Weight Each	Quantity
ST204B	1/2 in	Plastic Blue Tote	.030 in	5.1 lb	
	12.70 mm		.76 mm	2.4 kg	
ST205G	5/8 in	Plastic Green Tote	.030 in	6.4 lb	
	15.88 mm		.76 mm	3.0 kg	
ST206R	3/4 in	Plastic Red Tote	.030 in	7.7 lb	
	19.05 mm		.76 mm	3.6 kg	

Economy Coils for Lighter Duty Applications

Economy Cons for Lighter Buty Applications						
ltem #	Width	Material	Thickness	Weight Each	Quantity	
ST128904	1/2 in	Stainless Steel	.015 in	5.5 lb	200 ft/Coil	
	12.70 mm		.38 mm	2.5 kg]	
ST183914	1/2 in	Stainless Steel	.020 in	7.0 lb	200 ft/Coil	
	12.70 mm		.51 mm	3.2 kg		
ST184	1/2 in	Stainless Steel	.025 in	8.5 lb	200 ft/Coil	
	12.70 mm		.63 mm	3.6 kg		
ST129905	5/8 in	Stainless Steel	.015 in	6.4 lb	200 ft/Coil	
	15.88 mm		.38 mm	3.0 kg		
ST1295915	5/8 in	Stainless Steel	.020 in	8.5 lb	200 ft/Coil	
	15.88 mm		.51 mm	3.6 kg		
ST163916	3/4 in	Stainless Steel	.020 in	11.2 lb	200 ft/Coil	
	19.05 mm		.51 mm	5.1 kg		
ST165	3/4 in	Stainless Steel	.025 in	12.7 lb	200 ft/Coil	
	19.05 mm		.63 mm	5.8 kg		



Bigbinder™ Band - 201 Stainless Steel

ST430	3/4 in	Type 201 Stainless Steel	.044 in	11.6 lb	100 ft/Roll
	19.05 m		1.12 mm	5.4 kg	
	m				
ST431	1 in	Type 201 Stainless Steel	.044 in	13.7 lb	100 ft/Roll
	25.4 mm		1.12 mm	6.4 kg	
ST432	1-1/4 in	Type 201 Stainless Steel	.044 in	17.2 lb	100 ft/Roll
	31.8 mm		1.12 mm	8.0 kg	

Mill Wound Coils

Item #	Width	Wound	Thickness	Weight/ Coil	Quantity
BLCPX04155	1/2 in	Oscillate	.015 in	100 lb	3920 ft/Coil
305SSR900	1/2 in	Ribbon	.020 in	30 lb	900 ft/Coil
305SSV3000	1/2 in	Oscillate	.020 in	100 lb	3000 ft/Coil
311SSR900	3/4 in	Ribbon	.020 in	42 lb	900 ft/Coil
311SSV2000	3/4 in	Oscillate	.020 in	100 lb	2000 ft/Coil
BLCPX05202	5/8 in	Oscillate	.020 in	1 lb	2300 ft/Coil